

Rebling Datasheet: Forever Easy Adapter

The Forever Easy Adapter prevents injuries to female forklift drivers and eliminates the need to replace damaged contacts or cable for the lifetime of the lift truck. No one will strain their chest or arm muscles again while unplugging a connector and no one will harm your truck's connectors again by yanking on the cables. The Forever Easy Adapter snaps onto your existing battery charger's connector and reduces Unmating force by 80%. This adapter is designed for Battery Swap charging operations, not for charging operations where the battery is charged while it stays in the lift truck.

Performance Specifications

Current Rating	Per UL 1977	400 amps
Voltage Rating	Per UL 1977	600 volts
Flammability Rating:	Per UL 94	V-0
Operating Temperature Range		-40 to 105 C°
Compatible with Forklift Connector Style -----		SB350
For Un-Powered Circuit Disconnect Only		
For Battery Swap Charging Only		
Forever Easy Adapter Part # -----		LP350

Compliance

RoHS, REACH, CMRT/3TG

The P/N listed on this datasheet is RoHS, REACH and CMRT/3TG Compliant



To Install:

Look for the words "Locking Side" on the adapter and push that end into the connector attached to your charger until you hear it lock in place. When it's time to charge a battery, plug the battery's connector into the adapter. When the battery is fully charged and the charger turns off, a gentle pull on the battery's connector will unplug it.

← Charger



To Remove:

Pull on the adapter then either press down on the unlocking button with a screwdriver or insert a ball point pen through the mouth of the adapter and under the unlocking button until you hear a click, then pull the adapter off.

→ Pull Adapter

